

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

A PORTION OF THE

SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTIONS

2, 3, 10, 11, 14, 15, 22, 23, AND 26,

IN

TOWNSHIP 2 NORTH, RANGE 3 EAST

of the Salt Lake Meridian  
In the State of Utah

EXECUTED BY

*Ronald K. Baugh*  
*Supervisory Cadastral Surveyor*

Under special instructions dated *June 1, 1992, and April 14, 1995*, approved *June 1, 1992, and April 14, 1995 respectively*, which provided for the surveys included under Group Numbers 789 and 824, *Utah*, and assignment instructions dated *June 8, 1992 and June 6, 1995*.

Survey commenced *June 8, 1992*  
Survey completed *August 10, 1995*

## INDEX DIAGRAM

Township 2 North, Range 3 East.

			17	13	5
6	5	4	16 3	13 2	4 1
			15 16	11 12	4
7	8	9	15 10	11 11	3 12
			14	10 10	3
18	17	16	15	10 14	13
			14	8 9	
19	20	21	22	7 23	24
				6 7	3
30	29	28	27	6 26	3 25
				5 5	2
31	32	33	34	35	36

The Subdivision of Section 2.....	Page 17
The Subdivision of Section 3.....	Page 21
The Subdivision of Section 10.....	Page 23
The Subdivision of Section 11.....	Page 27
The Subdivision of Section 14.....	Page 34
The Subdivision of Section 15.....	Page 37
The Subdivision of Section 22.....	Page 40
The Subdivision of Section 23.....	Page 40
The Subdivision of Section 26.....	Page 43
Survey of a Portion of the East Canyon Reservoir through Section 11..	Page 30
Survey of a Portion of the East Canyon Reservoir through Section 23..	Page 42
Survey of a Portion of the East Canyon Reservoir through Section 26..	Page 45

## TOWNSHIP 2 NORTH, RANGE 3 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 2, 3, 10, 11, 14, 15, 22, 23, and 26 in Township 2 North, Range 3 East, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. or Resurveyed by		
NORTH BOUNDARY				
Portion	A.D. Ferron	1870		
All	F. Dickert	1881	F. Dickert	1881
Portion			R. Gorlinski	1893
SOUTH BOUNDARY				
All	F. Dickert	1881		
Portion			R. Gorlinski	1893
EAST BOUNDARY				
All	F. Dickert	1881		
Portion			R. Gorlinski	1896
WEST BOUNDARY				
Portion	F. Dickert	1881		
All	R. Gorlinski	1893-1894	R. Gorlinski	1893-1894
SUBDIVISION				
Portion	F. Dickert	1881		
Portion	R. Gorlinski	1894-1896	R. Gorlinski	1894-1896

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 789, dated June 1, 1992, and Group No. 824, dated April 14, 1995.

The directions of lines were determined by hour angle observations of the sun, and by the Global Positioning System (GPS), and carried forward by sustained angulation. Distances were determined by electronic measurement.

## TOWNSHIP 2 NORTH, RANGE 3 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the monuments and calls of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the SE corner of section 26, as determined by ties made to National Geodetic Survey triangulation station "LOCK", by Global Positioning System Method, and this position will also function as a B.L.M. Control Station, is as follows:

Latitude 40° 52' 00.971" N.      Longitude 111° 34' 12.054" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 14° E.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 2 N., R. 3 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed  
by F. Dickert in 1881 and the  
Retracement Executed by R. Gorlinski in 1894-1896)

---

Beginning at the corner of sections 25, 26, 35, and 36, monumented with a sandstone, 15x12x8 ins., in a small mound of stone, marked with 1 notch on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a mound of stone, with aluminum cap marked:

T2N	R3E
S26	S25
S35	S36

1995

Deposit the marked stone alongside the aluminum post and a Deep 1 Magnet at base of aluminum post.

Raise a mound of stone, 3 ft base, 2 ft. high, W of the corner.

Corner is located on rocky S slope about 90 lks. N of road.

This corner will also function as a B.L.M. Control Station, hereinbefore described.

N. 0° 00.3' E., between sections 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****38.872**

Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, falls in pond; there is no remaining evidence of the original corner; not monumented.

**77.744**

The corner of sections 23, 24, 25, and 26, at the corner of fences bearing N and E. There is no evidence of the original corner. This point is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T2N R3E	
S23	S24
S26	S25
1995	

Corner is located on SW slope in sagebrush and native grasses.

---

From the corner of sections 11, 12, 13, and 14, monumented with a sandstone, 20x12x8 ins., dimly marked with 1 groove on the E face and 4 grooves on the S face, in a mound of stone, at a fence corner, from which the fence bears N, S, and E.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T2N R3E	
S11	S12
S14	S13
1995	

N. 0° 10.3' W., between sections 11 and 12.

**39.908**

Point for the 1/4 section corner of sections 11 and 12, at proportionate distance, falls in a fence line bearing N and S. A rock fitting the size and type of stone had been moved when the new fence was built.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, with 4 ft. base, to top of aluminum cap marked:

T2N R3E	
1/4	
S 11	S 12
1995	

Corner is located on W slope in sagebrush.

**59.862**

Point for the N 1/16 section corner of sections 11 and 12; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****79.816**

The corner of sections 1, 2, 11, and 12, monumented with a sandstone, 13x6x4 ins., in a mound of stone with obliterated marks, by a fence corner, from which the fence bears E, W, and S.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T2N R3E	
S2	S1
S11	S12
1995	

N. 0° 45.2' E., between sections 1 and 2.

**10.027**

Point for the SS 1/64 section corner of sections 1 and 2; not monumented.

**20.054**

Point for the S 1/16 section corner of sections 1 and 2; not monumented.

**40.108**

Point for the 1/4 section corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T2N R3E	
1/4	
S2	S1
1995	

Corner is located on a rocky WSW slope in sagebrush and native grasses.

**80.216**

Point for the 80 1/16 section corner of sections 1 and 2, and the witness monument described in the 1881 survey, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E	
80 1/16	
S2	S1
1995	

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

Corner is located in grass on a spur sloping SSE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

108.893

The closing corner of sections 1 and 2, monumented with a sandstone, 16x8x8 ins., marked with 1 groove on E face and 5 grooves on W face, in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

S35	
S2	S1
C	C
T2N	R3E
1995	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of the corner.

Corner is located on ESE slope in sagebrush and grass.

From this corner, the corner of sections 35 and 36 only, T. 3 N., R. 3 E., monumented with a quartz stone, 16x8x7 ins., plainly marked with 1 notch on the E and 5 notches on the W edges, in a fence corner, bearing N and E, bears N. 89° 20.0' E., 7.984 chs. distance. Not remonumented.

---

From the 1/4 section corner of sections 26 and 35, monumented with a broken sandstone in a mound of stone, with a 1/2 in. rebar, and cap marked 1/4.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E	
1/4	S26
S35	
1995	

Deposit the corner stone and rebar alongside the aluminum post.

Corner is located on S slope about 75 lks. N of E and W road.

N. 89° 28.7' W., between sections 26 and 35.

19.480

Point for the W 1/16 section corner of sections 26 and 35; not monumented.

38.960

The corner of sections 26, 27, 34, and 35, monumented with a 1/2 in. rebar in line with a fence to the E. This corner is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E	
S27	S26
S34	S35
1995	

Deposit the 1/2 in. rebar alongside the aluminum post.

N. 0° 10.0' W., between sections 26 and 27.

38.830

The 1/4 section corner of sections 26 and 27, monumented with a prophry stone, 14x10x5 ins., dimly marked 1/4 on W face, and in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T2N R3E	
1/4	
S27	S26
1995	

Deposit the marked stone alongside the aluminum post.

Corner is located on a rocky NW slope in sagebrush and scattered oak.

N. 0° 07.7' W., beginning new measurement.

38.240

The corner of sections 22, 23, 26, and 27, monumented with a gray sandstone, 10x8x5 ins., firmly set under a sagebrush, marked with 2 notches on S edge only.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E	
S22	S23
S27	S26
1995	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located in bottom of small draw, draining SW.

From the corner of sections 23, 24, 25, and 26.

N. 89° 15.0' W., between sections 23 and 26.

**30.854** Intersect the East Canyon Reservoir Boundary Line; not monumented.

**39.532** Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

$$\begin{array}{r} \text{T2N R3E} \\ 1/4 \frac{\text{S23}}{\text{S26}} \\ 1995 \end{array}$$

Deposit a Deep 1 Magnet at the base of the aluminum post.

**59.298** Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

$$\begin{array}{r} \text{T2N R3E} \\ \text{W } 1/16 \frac{\text{S23}}{\text{S26}} \\ 1995 \end{array}$$

Set a steel fence post alongside the aluminum post.

Corner is located on ENE slope in oak and sagebrush.

**79.064** The corner of sections 22, 23, 26, and 27.

N. 0° 01.9' W., between sections 22 and 23.

**19.640** Point for the S 1/16 section corner of sections 22 and 23; not monumented.

**39.280** The 1/4 section corner of sections 22 and 23, monumented with a sandstone, 15x10x10 ins., plainly marked 1/4 on the W face, with a 12 in. stake E of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T2N R3E  
1/4  
S22 | S23  
1992

Deposit the marked stone alongside the aluminum post.

N. 0° 28.5' W., beginning new measurement.

**20.047** Point for the N 1/16 section corner of sections 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, with 3 ft. base to top of aluminum cap marked:

T2N R3E  
N 1/16  
S22 | S23  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on E slope in sage and grass.

Corner is 1.5 lks. south of E and W fence line.

**40.094** The corner of sections 14, 15, 22, and 23, monumented with a broken sandstone, 18x10x8 ins., dimly marked.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 4 ft. base, with aluminum cap marked:

T2N R3E  
S15 | S14  
S22 | S23  
1992

Deposit the marked stone alongside the aluminum post.

The corner is located in an old fence which projects S and W, and is covered with water in the spring.

From the 1/4 section corner of sections 14 and 23, monumented with a sandstone, 16x12x7 ins., plainly marked with an upside down 1/4 on the E face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
1/4  $\frac{S14}{S23}$   
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

S. 89° 52.5' W., between sections 14 and 23.

**19.575** Point for the W 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 26 ins. in the ground, and a steel fence post alongside, with aluminum cap marked:

T2N R3E  
W 1/16  $\frac{S14}{S23}$   
1995

**20.348** Point for the witness point at intersection with the east right-of-way line of Utah State Highway No. 65.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

WP  
AP10  $\frac{S14}{S23}$   
1995

Set a steel fence post alongside the aluminum post.

This corner will also function as Angle Point No. 10 of the East Canyon Reservoir Boundary.

**39.150** The section corner of sections 14, 15, 22, and 23.

---

N. 0° 26.6' W. between sections 14 and 15.

**20.083** Point for the S 1/16 section corner of sections 14 and 15, falls in East Canyon Reservoir; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

**40.166** Point for the 1/4 section corner of sections 14 and 15, at proportionate distance, falls in East Canyon Reservoir; not monumented.

**60.249** Point for the N 1/16 section corner of sections 14 and 15; falls in East Canyon Reservoir; not monumented.

**80.332** Point for the corner of sections 10, 11, 14, and 15, at proportionate distance, falls in East Canyon Reservoir; not monumented.

From the 1/4 section corner of sections 11 and 14, monumented with a sandstone, 18x18x18 ins., marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 13 ins. in the ground to bedrock, and in a mound of stone, 5 ft. to top of cap, with aluminum cap marked:

T2N R3E  
1/4  $\frac{S11}{S14}$   
1992

Deposit the marked stone alongside the aluminum post.

S. 89° 25.9' W. between sections 11 and 14.

**20.004** Point for the W 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T2N R3E  
W 1/16  $\frac{S11}{S14}$   
1992

**24.586** Point for the witness point at intersection with the east right-of-way line of Utah State Highway No. 65 and Parcel 2B of the Bureau of Reclamation Plat.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, with 3 ft. base, to top of aluminum cap marked:

WP  
 $\frac{S11}{S14}$   
1992

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

This corner will also function as Angle Point No. 1 of the East Canyon Reservoir Boundary through section 11.

**40.008** True point for the corner of sections 10, 11, 14, and 15; not monumented.

N. 0° 24.8' W. between sections 10 and 11.

**20.158** Point for the S 1/16 section corner of sections 10 and 11, falls in East Canyon Reservoir; not monumented.

**40.316** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance, falls in East Canyon Reservoir; not monumented.

**60.474** Point for the N 1/16 section corner of sections 10 and 11, falls in East Canyon Reservoir; not monumented.

**80.632** The corner of sections 2, 3, 10, and 11, monumented with a quartzite, 16x14x10 ins., marked with 5 grooves on the S face and 2 grooves on the E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T2N	R3E
S3	S2
S10	S11
1992	

Deposit the marked stone alongside the aluminum post.

From the corner of sections 1, 2, 11, and 12.

S. 89° 39.7' W., between sections 2 and 11.

**5.004** Point for the E-E-E 1/256 section corner of sections 2 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

E-E-E 1/256	T2N R3E
	S2
	S11
	1995

Corner is in an E and W fence line.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

20.016

Point for the E 1/16 section corner of sections 2 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	T2N R3E
E 1/16	<u>S2</u>
	S11
	1995

40.032

Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T2N R3E
1/4	<u>S2</u>
	S11
	1995

Deposit a Deep 1 Magnet at base of aluminum post.

Corner is located on ESE slope covered with sagebrush and native grasses.

Set a steel fence post alongside the aluminum post.

60.048

Point for the W 1/16 section corner of sections 2 and 11, falls in west lane of State Highway No. 65, bears NNE and SSW.

Set a railroad spike in the asphalt road with indentation on top of spike.

80.064

The corner of sections 2, 3, 10, and 11.

---

N. 2° 04.0' E., between sections 2 and 3.

10.072

Point for the S-S 1/64 section corner of sections 2 and 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

	T2N R3E
S-S	1/64
S3	S2
	1995

Corner is located on W slope in grass.

20.144

Point for the S 1/16 section corner of sections 2 and 3; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.288

The 1/4 section corner of sections 2 and 3, monumented with a quartzite, 12x10x10 ins. firmly set and marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
1/4  
S3 | S2  
1995

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

Corner is located about 75 lks. E of draw, draining S.

---

N. 0° 53.9' E., beginning new measurement.

39.910

The original witness corner of sections 2 and 3 on the offset line for the north boundary, of the 1881 survey, monumented with a quartz stone, 18x10x10 ins., set in a mound of stone and marked with 2 grooves on E face, 4 grooves on W face, and 6 grooves on the N and S faces.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

WC  
T2N R3E  
S3 | S2  
1995

Deposit a Deep 1 Magnet at base of aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located on steep E slope in scattered mahogany and native grass.

---

From the corner of sections 14, 15, 22, and 23.

N. 89° 03.8' W. between sections 15 and 22.

19.864

Point for the E 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T2N R3E  
E 1/16  $\frac{S15}{S22}$   
1995

Set a steel fence post alongside the aluminum post.

Corner is located on NW slope in sage and grass.

39.728

The 1/4 section corner of sections 15 and 22, monumented with a sandstone, 16x12x8 ins., plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
1/4  $\frac{S15}{S22}$   
1992

Deposit the marked stone alongside the aluminum post.

From the point for the section corner of sections 10, 11, 14, and 15; not monumented.

N. 89° 29.4' W. between sections 10 and 15.

19.468

Point for the E 1/16 section corner of sections 10 and 15; falls in East Canyon Reservoir; not monumented.

34.069

Point for the W-W-E 1/256 section corner of sections 10 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E  
W-W-E 1/256  $\frac{S10}{S15}$   
1995

Set a steel fence post alongside the aluminum post.

Corner is located on steep ENE slope in sage and scattered oak.

38.936

The 1/4 section corner of sections 10 and 15, monumented with a quartzite, 12x10x8 ins., plainly marked 1/4 on the N face.

At the corner point



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T2N R3E  
1/4 S10  
S15  
1992

Deposit the marked stone alongside the aluminum post.

From the 1/4 section corner of sections 9 and 10, monumented with a quartzite, 18x8x8 ins., firmly set and marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
1/4  
S9 | S10  
1995

Deposit the marked stone alongside the aluminum post, with a Deep 1 Magnet at base.

Corner is located on a NNW slope covered with oak.

N. 1° 43.8' W., between sections 9 and 10.

**20.647** Point for the N 1/16 section corner of sections 9 and 10; not monumented.

**41.294** The corner of sections 3, 4, 9, and 10, monumented with a 1/2 in. rebar, 18 ins. long, in a mound of stone. There were no marked stones found. This rebar is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E  
S4 | S3  
S9 | S10  
1995

Deposit the rebar inside the aluminum post.

Corner is located on steep SW slope in scattered oak and sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 2, 3, 10, and 11.

N. 89° 40.9' W., between sections 3 and 10.

**19.648** Point for the E 1/16 section corner of sections 3 and 10; not monumented.

**24.560** Point for the E-W-E 1/256 section corner of sections 3 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

	T2N R3E
E-W-E 1/256	S3
	S10
	1995

Corner is located on steep ESE slope in sagebrush and native grass.

**39.296** Point for the 1/4 section corner of sections 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T2N R3E
1/4	S3
	S10
	1995

Corner is located on rocky ESE slope.

**58.944** Point for the W 1/16 section corner of sections 3 and 10; not monumented.

**78.592** The corner of sections 3, 4, 9, and 10.

---

N. 0° 53.4' E., between sections 3 and 4.

**39.049** Point for the 1/4 section corner of sections 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T2N R3E
	1/4
S4	S3
	1995

Corner is located on SE slope covered with oak and sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**78.878**

The original witness corner of sections 3 and 4 on the offset line for the north boundary, of the 1881 survey, monumented with a quartz stone, 18x10x8 ins., firmly set and marked with grooves on the faces, 3 each on E and W, and 6 each on N and S.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC  
T2N R3E  
S4 | S3  
1995

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 ft. high, W of the corner.

Corner is located on rocky W slope, about 30 lks. W of top of spur, bears N and S.

---

The Subdivision of Section 2,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

---

From the 80 1/16 section corner and witness monument of sections 1 and 2.

S. 89° 37.5' W., along the offset line for the north boundary in section 2, of the 1881 survey.

**39.510**

Point for the witness 1/4 section corner on the offset line for the north boundary of section 2 of the 1881 survey, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

WC  
T2N R3E  
1/4  
S2  
1995

Raise a mound of stone, 3 ft. base, 1/2 ft. high, N of the corner.

Corner is located on SE slope covered with sagebrush, native grass, and scattered oak.

**79.020**

The witness corner on offset line for the north boundary of sections 2 and 3.

---

THE SUBDIVISION OF SECTION 2,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- From the 1/4 section corner of sections 2 and 11.  
N. 1° 07.3' E., on the N-S center line of section 2.
- 20.095** Point for the center S 1/16 section corner; not monumented.
- 40.190** Point for the center 1/4 of section corner of section 2, at intersection with the E-W center line.  
  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:
- T2N R3E  
C 1/4  
S2  
1995
- Corner is located on WSW slope in sagebrush and native grass.
- 80.204** The witness 1/4 section corner on the offset line for the north boundary of section 2.
- 
- From the 1/4 section corner of sections 1 and 2.  
S. 89° 46.3' W., on the E-W center line of section 2.
- 19.885** Point for the center E 1/16 section corner; not monumented.
- 39.770** The center 1/4 section corner of section 2.
- 59.448** Point for the center W 1/16 section corner of section 2; not monumented.
- 79.126** The 1/4 section corner of sections 2 and 3.
- 
- From the E 1/16 section corner of sections 2 and 11.  
N. 0° 56.2' E., on the N-S center line of the SE 1/4 of section 2.
- 10.037** Point for the center S-SE 1/64 section corner; not monumented.
- 20.074** Point for the SE 1/16 section corner at intersection with the E-W center line of the SE 1/4; not monumented.
- 40.149** Point for the center E 1/16 section corner of section 2; not monumented.
-

THE SUBDIVISION OF SECTION 2,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the S 1/16 section corner of sections 1 and 2; not monumented.

S. 89° 43.0' W., on the E-W center line of the SE 1/4 of section 2.

**19.950** Point for the SE 1/16 section corner; not monumented.

**39.900** Point for the center S 1/16 section corner of section 2; not monumented.

From the point for the S-S 1/64 section corner of sections 1 and 2; not monumented.

S. 89° 41.3' W., on the E-W center line of the SE 1/4 of the SE 1/4 of section 2.

**4.996** Point for the center E-SE-SE 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-SE-SE 1/256  
S2  
1995

Corner is located about 1.06 chs. distance E of a draw, draining SSE and on a SW slope in native grass and sagebrush.

**9.992** Point for the SE-SE 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap marked:

T2N R3E  
SE-SE 1/64  
S2  
1995

Deposit a Deep 1 Magnet at base of aluminum post.

Corner is located 3 lks. N of a dirt road, which bears E and W, and 1.06 chs. W of State Highway No. 65, bears NNE and SSW.

**19.984** The point for the center S-SE 1/64 section corner of section 2; not monumented.

From the E-E-E 1/256 section corner of sections 2 and 11.

N. 0° 48.0' E., on the N-S center line of the SE 1/4, of the SE 1/4, of the SE 1/4 of section 2.

**10.030** The center E-SE-SE 1/256 section corner of section 2.

THE SUBDIVISION OF SECTION 2,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the SE-SE 1/64 section corner of section 2.

S. 45° 11.2' W., on the East Canyon Reservoir Boundary Line.

**14.316** The E 1/16 section corner of sections 2 and 11.

From the W 1/16 section corner of sections 2 and 11.

N. 1° 35.7' E., on the N-S center line of the SW 1/4 of section 2.

**10.084** Point for the center S-SW 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-S-SW 1/64  
S2  
1995

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

**20.168** Point for the SW 1/16 section corner, at intersection with the E-W center line of the SW 1/4; not monumented.

**40.336** Point for the center W 1/16 section corner of section 2; not monumented.

From the point for the center S 1/16 section corner of section 2; not monumented.

S. 89° 43.0' W., on the E-W center line of the SW 1/4 of section 2.

**19.597** The point for the SW 1/16 section corner; not monumented.

**39.194** Point for the S 1/16 section corner of sections 2 and 3; not monumented.

From the center S-SW 1/64 section corner of section 2.

S. 89° 41.3' W. on the E-W center line of the SW 1/4 of the SW 1/4 of section 2.

**19.806** The S-S 1/64 section corner of sections 2 and 3.

THE SUBDIVISION OF SECTION 3,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

The Subdivision of Section 3,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the witness corner of sections 2 and 3, for the north boundary offset line, of the township.

S. 89° 22.7' W., along the offset line for the north boundary in section 3, of the 1881 survey.

**39.720** Point for the witness 1/4 section corner on the offset line for the north boundary of section 3 of the 1881 survey, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

WC	
1/4	S3
1995	

Corner is located on steep S slope in scattered oak and sagebrush.

**79.440** The witness corner on the offset line for the north boundary of sections 3 and 4.

From the 1/4 section corner of sections 3 and 10.

N. 1° 11.3' E., on the N-S center line of section 3.

**19.830** Point for the center S 1/16 section corner of section 3; not monumented.

**39.660** Point for the center 1/4 section corner of section 3, at intersection with the E-W center line; not monumented.

**79.534** The witness 1/4 section corner on the offset line for the north boundary of section 3.

From the 1/4 section corner of sections 2 and 3.

S. 89° 26.2' W., on the E-W center line of section 3.

**19.962** Point for the center E 1/16 section corner; not monumented.

**39.924** Point for the center 1/4 section corner of section 3; not monumented.

**79.440** The 1/4 section corner of sections 3 and 4.

THE SUBDIVISION OF SECTION 3,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the E 1/16 section corner of sections 3 and 10; not monumented.

N. 1° 37.7' E., on the N-S center line of the SE 1/4 of section 3.

**9.993** Point for the center S-SE 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-S-SE 1/64  
S3  
1995

**19.986** Point for the SE 1/16 section corner, at intersection with the E-W center line of the SE 1/4 of section 3; not monumented.

**39.973** Point for the center E 1/16 section corner; not monumented.

From the point for the S 1/16 section corner of sections 2 and 3; not monumented.

S. 89° 52.7' W., on the E-W center line of the SE 1/4 of section 3.

**4.951** Point for the center E-E-SE 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-E-SE 1/256  
S3  
1995

Corner is located on a grassy SSW slope about 30 lks. E of a steep drop off.

**14.853** Point for the center W-E-SE 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-W-E-SE 1/256  
S3  
1995

Corner is located on a steep NE slope in sagebrush, native grass, and oak brush, 8 lks. S of small draw, drains SE.

**19.804** Point for the SE 1/16 section corner of section 3; not monumented.



THE SUBDIVISION OF SECTION 3,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.608

Point for the center S 1/16 section corner of section 3; not monumented.

From the S-S 1/64 section corner of sections 2 and 3.

N. 89° 54.1' W., on the E-W center line of the SE 1/4 of the SE 1/4 of section 3.

4.931

Point for the center E-SE-SE 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-SE-SE 1/256  
S3  
1995

19.724

The center S-SE 1/64 section corner of section 3.

From the center E-SE-SE 1/256 section corner of section 3.

N. 1° 57.4' E., on the N-S center line of the NE 1/4 of the SE 1/4 of the SE 1/4 of section 3.

10.052

The center E-E-SE 1/256 section corner of section 3.

From the center W-E-SE 1/256 section corner of section 3.

S. 27° 38.0' W., on East Canyon Reservoir Boundary Line.

11.287

The center S-SE 1/64 section corner of section 3.

S. 27° 32.8' W., on the East Canyon Reservoir Boundary Line.

11.235

The E-W-E 1/256 section corner of sections 3 and 10.

The Subdivision of Section 10,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0° 40.6' W., on the N-S center line of section 10.

19.854

Point for the center S 1/16 section corner; not monumented.

THE SUBDIVISION OF SECTION 10,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 39.708** Point for the center 1/4 section corner of section 10, at intersection with the E-W center line.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
C 1/4  
S10  
1995

Deposit 2 Deep 1 Magnets at base on E and W side of aluminum post.

Corner is located on steep N slope in oak.

- 49.908** Point for the center S-N 1/64 section corner falls in East Canyon Reservoir; not monumented.

- 60.108** Point for the center N 1/16 section corner falls in East Canyon Reservoir; not monumented.

- 65.208** Point for the center S-N-N 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E  
C  
S-N-N 1/256 | S10  
C  
1995

Corner is located on steep S slope in sagebrush and native grass.

- 80.508** The 1/4 section corner of sections 3 and 10.

---

From the point for the 1/4 section corner of sections 10 and 11; not monumented.

S. 89° 36.8' W., on the E-W center line of section 10.

- 39.112** The center 1/4 section corner of section 10.

- 58.384** Point for the center W 1/16 section corner; not monumented.

- 77.656** The 1/4 section corner of sections 9 and 10.

---

From the point for the S 1/16 section corner of sections 10 and 11; not monumented.

THE SUBDIVISION OF SECTION 10,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89° 57.2' W., on the E-W center line of the SE 1/4 of section 10.

**34.146**

Point for the center W-W-SE 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-W-W-SE 1/256  
S10  
1995

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of the corner.

Set a steel fence post alongside the aluminum post.

Corner is located on E slope in sagebrush and native grass.

**39.024**

Point for the center S 1/16 section corner of section 10; not monumented.

From the W-W-E 1/256 section corner of sections 10 and 15.

N. 0° 38.6' W., on the N-S center line of the W 1/2 of the SW 1/4 of the SE 1/4 of section 10.

**19.892**

The center W-W-SE 1/256 section corner of section 10.

N. 14° 26.0' W., on the East Canyon Reservoir Boundary Line.

**20.511**

The center 1/4 section corner of section 10.

From the point for the center W 1/16 section corner of section 10.

N. 1° 12.2' W., on the N-S center line of the NW 1/4 of section 10.

**10.253**

Point for the center S-NW 1/64 section corner; not monumented.

**20.506**

Point for the NW 1/16 section corner, at intersection with the E-W center line of the NW 1/4; not monumented.

**25.633**

Point for the center S-N-NW 1/256 section corner; not monumented.

**41.014**

Point for the W 1/16 section corner of sections 3 and 10; not monumented.

THE SUBDIVISION OF SECTION 10,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the point for the center N 1/16 section corner of section 10, not monumented.

S. 89° 58.0' W., on the E-W center line of the NW 1/4 of section 10.

**12.160** Intersect the East Canyon Reservoir Boundary Line on W side of reservoir; not monumented.

**19.456** Point for the NW 1/16 section corner; not monumented.

**38.916** Point for the N 1/16 section corner of sections 9 and 10; not monumented.

---

From the center S-N-N 1/256 section corner of section 10.

N. 89° 56.7' W., on the E-W center line of the S 1/2 of the NE 1/4 of the NW 1/4 of section 10.

**12.190** Point for the center E-SW-NE-NW 1/1024 section corner section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top aluminum cap marked:

1/1024  
S10  
1995

**19.504** Point for the S-N-NW 1/256 section corner in section 10; not monumented.

---

From the point for the center S-N 1/64 section corner of section 10; not monumented.

S. 89° 47.4' W., on the E-W center line of the SE 1/4 of the NW 1/4 of section 10.

**9.684** Point for the SE-NW 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 2 1/2 ft. base to top of aluminum cap marked:

T2N R3E  
SE-NW 1/64  
S10  
1995

Corner is located on a steep N slope in oak, mahogany and sagebrush.

**12.105** Point for the center E-W-SE-NW 1/1024 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 10,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

1/1024  
S10  
1995

Corner is located on a rocky steep NNW slope covered with oak and sagebrush S of dam.

19.368

Point for the center S-NW 1/64 section corner of section 10; not monumented.

From the center E-W-SE-NW 1/1024 section corner of section 10.

N. 1° 00.3' W., on the N-S center line of the E 1/2 of the W 1/2 of the E 1/2 of the NW 1/4 of section 10.

10.233

Intersect the E-W center line of the NW 1/4; not monumented.

15.350

The center E-SW-NE-NW 1/1024 section corner of section 10.

From the center 1/4 section corner of section 10.

N. 43° 58.1' W., on the East Canyon Reservoir Boundary Line.

14.122

The SE-NW 1/64 section corner of section 10.

The Subdivision of Section 11,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 11 and 14.

N. 0° 23.6' W., on the N-S center line of section 11.

31.925

Intersect the East Canyon Reservoir Boundary Line; not monumented.

40.358

Point for the center 1/4 section corner of section 11, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
C 1/4  
S11  
1995

Placed a large boulder, 24x24x18 ins., on the W side of corner,

THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located 12 lks. E of high water mark of East Canyon Reservoir on a W slope covered with sagebrush and native grass.

**60.418** Point for the center N 1/16 section corner; not monumented.

**70.448** Point for the center N-N 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C  
N-N 1/64 | S11  
C  
1995

Corner is located on an ESE slope in sagebrush and native grass.

**80.478** The 1/4 section corner of sections 2 and 11.

---

From the 1/4 section corner of sections 11 and 12.

S. 89° 22.1' W., on the E-W center line of section 11.

**19.942** Point for the center E 1/16 section corner; not monumented.

**30.644** Intersect the East Canyon Reservoir Boundary Line; not monumented.

**39.884** The center 1/4 section corner of section 11.

**59.893** Point for the center W 1/16 section corner, falls in East Canyon Reservoir; not monumented.

**79.902** Point for the 1/4 section corner of sections 10 and 11; not monumented.

---

From the point for the center E 1/16 section corner of section 11; not monumented.

N. 0° 17.0' W., on the N-S center line of the NE 1/4 of section 11.

**12.384** Intersect the East Canyon Reservoir Boundary Line, on a curve to the left; not monumented.

**20.008** Point for the NE 1/16 section corner, at intersection with the E-W center line of the NE 1/4 of section 11; not monumented.

**30.012** Point for the center N NE 1/64 section corner, falls in East Canyon Reservoir; not monumented.

THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 40.016** The E 1/16 section corner of sections 2 and 11.
- 
- From the point for the N 1/16 section corner of sections 11 and 12; not monumented.
- S. 89° 30.9' W., on the E-W center line of the NE 1/4 of section 11.
- 18.311** Intersect the East Canyon Boundary Line; not monumented.
- 19.980** Point for the NE 1/16 section corner; not monumented.
- 39.960** Point for the center N 1/16 section corner of section 11; not monumented.
- 
- From the point for the center N-NE 1/64 section corner of section 11; not monumented.
- S. 89° 35.3' W., on the E-W center line of the NW 1/4 of the NE 1/4 of section 11.
- 9.999** Point for the NW-NE 1/64 section corner of section 11.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:
- T2N R3E  
NW-NE 1/64  
S11  
1995
- Corner is located on SE slope in sagebrush and native grass.
- 19.998** The center N-N 1/64 section corner of section 11.
- 
- From the E 1/16 section corner of sections 2 and 11.
- S. 44° 38.1' W., on the East Canyon Reservoir Boundary Line.
- 14.160** The NW-NE 1/64 section corner of section 11.
- 
- From the point for the center W 1/16 section corner of section 11; not monumented.
- N. 0° 24.2' W., on the N-S center line of the NW 1/4 of section 11.
- 20.110** Point for the NW 1/16 section corner, at intersection with the E-W center line of the NW 1/4 of section 11; not monumented.
- 30.165** Point for the center N-NW 1/64 section corner of section 11.

THE SUBDIVISION OF SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T2N R3E  
C-N-NW 1/64  
S11  
1995

**40.220** The W 1/16 section corner of sections 2 and 11.

From the point for the center N 1/16 section corner of section 11; not monumented.

S. 89° 30.9' W., on the E-W center line of the NW 1/4 of section 11.

**20.012** The point for the NW 1/16 section corner; not monumented.

**40.024** Point for the N 1/16 section corner of sections 10 and 11; not monumented.

From the center N-N 1/64 section corner of section 11.

S. 89° 35.3' W., on the E-W center line of the NE 1/4 of the NW 1/4 of section 11.

**20.014** The center N-NW 1/64 section corner of section 11.

Survey of a Portion of the Boundary of the East Canyon  
Reservoir Through Section 11,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the witness point between sections 11 and 14, on the East Canyon Reservoir Boundary Line. This corner will also function as Angle Point No. 1, herinbefore described.

Thence N. 25° 04.8' W., on the East Canyon Reservoir Boundary Line through section 11.

**9.453** Point for Angle Point No. 2.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-2 S11  
1995

Set a steel fence post alongside the aluminum post.




SURVEY OF A PORTION OF THE BOUNDARY OF THE EAST CANYON  
RESERVOIR THROUGH SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Thence N.  $16^{\circ} 07.3' E.$ , on the ECR-Bdy.

**12.491** Point for Angle Point No. 3, identical to the P.C. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:




Set a steel fence post alongside the aluminum post.

Thence on curve to right, with:

Delta =  $31^{\circ} 34' 47''$ , R = 10.681, T = 3.020, L = 5.887,  
CB = S.  $81^{\circ} 00.0' E.$ , and C = 5.813.

**5.887** Point for Angle Point No. 4, identical to the P.T. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.

Thence S.  $65^{\circ} 12.8' E.$ , on the ECR-Bdy.

**4.880** Point for Angle Point No. 5, identical to the P.C. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.

Thence on curve to left, with:


Delta =  $109^{\circ} 07' 49''$ , R = 6.818, T = 9.582, L = 12.986,  
CB = N.  $60^{\circ} 13.6' E.$ , and C = 11.110.

**12.986** Point for Angle Point No. 6, identical to the P.T. of curve.

SURVEY OF A PORTION OF THE BOUNDARY OF THE EAST CANYON  
RESERVOIR THROUGH SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:




Set a steel fence post alongside the aluminum post.

Thence N. 5° 39.2' E., on the ECR-Bdy.

**2.112** Point for Angle Point No. 7, identical to the P.C. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:




Set a steel fence post alongside the aluminum post.

Thence on curve to right, with:

Delta = 41° 25' 37", R = 7.064, T = 2.671, L = 5.107,  
CB = N. 26° 22.4' E, and C = 4.997.

**5.107** Point for Angle Point No. 8, identical to the P.T. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.

Thence N. 47° 05.5' E., on the ECR-Bdy.

**3.632** Intersect the N-S center line; not monumented.

**16.168** Intersect the E-W center line; not monumented.

**19.383** Point for Angle Point No. 9, identical to the P.C. of curve.

SURVEY OF A PORTION OF THE BOUNDARY OF THE EAST CANYON  
RESERVOIR THROUGH SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

ECR-B  
AP-9 } S11  
1995

Thence on a curve to left, with:

Delta =  $18^{\circ} 24' 54''$ , R = 47.194, T = 7.650, L = 15.168,  
CB = N.  $37^{\circ} 53.3'$  E, and C = 15.103.

**13.253** Intersect the N-S center line of the NE 1/4; not monumented.

**15.168** Point for Angle Point No. 10, identical to the P.T. of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-10 } S11  
1995

Set a steel fence post alongside the aluminum post.

Thence N.  $2^{\circ} 05.7'$  E., on the ECR-Bdy.

**5.080** Point for Angle Point No. 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-11 } S11  
1995

Set a steel fence post alongside the aluminum post.

Thence N.  $28^{\circ} 40.8'$  E., on the ECR-Bdy.

**1.027** Intersect the E-W center line of the NE 1/4; not monumented.

**15.065** Point for Angle Point No. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SURVEY OF A PORTION OF THE BOUNDARY OF THE EAST CANYON  
RESERVOIR THROUGH SECTION 11,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

ECR-B  
AP-12 / S11  
1995

Set a steel fence post alongside the aluminum post.

Thence N. 55° 14.8' E. on the ECR-Bdy.

**5.082** Point for Angle Point No. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-13 / S11  
1995

Thence N. 28° 41.0' E. on the ECR-Bdy.

**1.515** Point for Angle Point No. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-14 / S11  
1995

Set a steel fence post alongside the aluminum post.

Thence N. 23° 35.8' E. on the ECR-Bdy.

**3.915** The E-E-E 1/256 section corner of sections 2 and 11.

---

The Subdivision of Section 14,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 14 and 23.

N. 0° 10.3' E., on the N-S center line of section 14.

**10.094** Point for the center S-S 1/64 section corner, not monumented.

THE SUBDIVISION OF SECTION 14,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 20.188** Point for the center S 1/16 section corner; not monumented.
- 40.376** Point for the center 1/4 section corner at the intersection with the E-W center line.  
  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap marked:
- T2N R3E  
C 1/4 S14  
1992
- Raise a mound of stone west of the corner.
- 80.642** The 1/4 section corner of sections 11 and 14.
- 
- From the 1/4 section corner of sections 13 and 14, monumented with a sandstone, 12x6x6 ins., plainly marked with 1/4 on W face.
- At the corner point
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:
- T2N R3E  
1/4  
S14 | S13  
1992
- Corner is located in N and S fence line.
- S. 89° 34.5' W., on the E-W center line of section 14.
- 39.456** The center 1/4 section corner of section 14.
- 59.246** Point for the center W 1/16 section corner of section 14.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T2N R3E  
C W 1/16 C  
S14  
1992
- Raise a mound of stone N of the corner.

THE SUBDIVISION OF SECTION 14,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

79.036

Point for the 1/4 section corner of sections 14 and 15; not monumented.

---

From the W 1/16 section corner of sections 14 and 23.

N. 0° 08.1' W., on the N-S center line of the SW 1/4 of section 14.

10.068

Point for the center S-SW 1/64 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-S-SW 1/64  
S14  
1995

Set a steel fence post alongside aluminum post.

20.136

Point for SW 1/16 section corner at intersection with the E-W center line of the SW 1/4 of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
SW 1/16  
S14  
1992

Raise a mound of stone south of the corner.

40.271

The center W 1/16 section corner of section 14.

---

From the point for the center S 1/16 section corner of sections 14; not monumented.

S. 89° 43.3' W., on the E-W center line of the SW 1/4 of section 14.

4.921

Point for the center E-E-SW 1/256 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-E-SW 1/256  
S14  
1995

THE SUBDIVISION OF SECTION 14,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post alongside the aluminum post.

**19.684** The SW 1/16 section corner.

**39.367** Point for the S 1/16 section corner of sections 14 and 15; not monumented.

From the point for the center S-S 1/64 section corner of section 14; not monumented.

S. 89° 47.9' W., on the E-W center line of the SE 1/4 of the SW 1/4.

**4.907** Point for the center E-SE-SW 1/256 section corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-SE-SW 1/256  
S14  
1995

Set a steel fence post alongside the aluminum post.

**19.628** The center S-SW 1/64 section corner.

From the center E-SE-SW 1/256 section corner of section 14.

N. 0° 05.7' E., on the N-S center line of the NE 1/4 of the SE 1/4 of the SW 1/4 of section 14.

**10.088** The center E-E-SW 1/256 section corner.

From the center W 1/16 section corner of section 14.

N. 0° 08.1' W., on the N-S center line of the NW 1/4 of section 14.

**40.216** The W 1/16 section corner of sections 11 and 14.

The Subdivision of Section 15,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0° 06.9' E., on the N-S center line of section 15.

THE SUBDIVISION OF SECTION 15,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 9.985** Point for the center S-S 1/64 section corner of section 15; not monumented.
- 39.940** Point for the center 1/4 section corner of section 15, at intersection with the E-W center line.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:  
  

T2N R3E  
C 1/4  
S15  
1995

Set a steel fence post alongside the aluminum post.  
Corner is located on E slope in sagebrush and native grass.
- 80.027** The 1/4 section corner of sections 10 and 15.  
  


---

From the point for the 1/4 section corner of sections 14 and 15.  
N. 89° 22.9' W., on the E-W center line of section 15.
- 19.664** Point for the center E 1/16 section corner; not monumented.
- 24.580** Point for the center E-W-E 1/256 section corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:  
  

T2N R3E  
C-E-W-E 1/256  
S15  
1995

Set a steel fence post alongside the aluminum post.  
Corner is located on a NE slope in sagebrush and native grass.  
From this corner, a 1/2 in. rebar with a yellow cap marked MT WEST SURV ROY UTAH, bears S. 24° 05.6' W., 0.147 chs. dist.
- 34.412** Point for the center W-W-E 1/256 section corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:



THE SUBDIVISION OF SECTION 15,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

T2N R3E  
C-W-W-E 1/256  
S15  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on W slope in sagebrush and native grass.

**39.328** The center 1/4 section corner of section 15.

**78.704** The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 16x12x8 ins., firmly set in a small mound of stone and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E  
1/4  
S16 | S15  
1995

Deposit the marked stone alongside the aluminum post.

Corner is located on SE slope in heavy oak.

---

From the center W-W-E 1/256 section corner of section 15.

N. 0° 04.7' E., on the N-S center line of the W 1/2 of the W 1/2 of the NE 1/4 of section 15.

**40.097** The W-W-E 1/256 section corner of sections 10 and 15.

---

From the E 1/16 section corner of sections 15 and 22.

N. 0° 09.7' W., on the N-S center line of the SE 1/4 of section 15.

**10.013** Point for the center S-SE 1/64 section corner; not monumented.

**40.052** Point for the center E 1/16 section corner of section 15; not monumented.

---

From the point for the center S-SE 1/64 section corner of section 15; not monumented.

N. 89° 08.5' W. on the E-W center line of the SW 1/4 of the SE 1/4 of section 15.

**4.953** Point for the center E-SW-SE 1/256 section corner.

THE SUBDIVISION OF SECTION 15,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-E-SW-SE 1/256  
S15  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on E slope in sagebrush and native grass.

From this corner, a 1/2 in. rebar with a yellow cap marked MT WEST SURV ROY UTAH, bears S. 52° 43.3' W., 0.202 chs. dist.

**19.812** Point for the center S-S 1/64 section corner of section 15; not monumented.

---

From the E 1/16 section corner of sections 15 and 22.

N. 26° 16.5' W., on the East Canyon Reservoir Boundary Line.

**11.250** The center E-SW-SE 1/256 section corner of section 15.

---

N. 0° 05.5' W., on the N-S center line of the E 1/2 of the W 1/2 of the SE 1/4 of section 15.

**30.019** The center E-W-E 1/256 section corner of section 15.

---

The Subdivision of Section 22,  
T. 2 N., R. 3 E. Salt Lake Meridian, Utah

---

From the N 1/16 section corner of sections 22 and 23.

N. 44° 30.6' W., on the East Canyon Reservoir Boundary Line.

**28.568** The E 1/16 section corner of sections 15 and 22.

---

The Subdivision of Section 23,  
T. 2 N., R. 3 E. Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 23 and 26.

N. 0° 30.9' W., on the N-S center line of section 23.

THE SUBDIVISION OF SECTION 23,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

- 19.788** Point for the center S 1/16 section corner; not monumented.
- 36.331** Intersect the East Canyon Reservoir Boundary Line; not monumented.
- 39.576** Point for the center 1/4 section corner of section 23, at intersection with the E-W center line, not monumented.
- 79.974** The 1/4 section corner of sections 14 and 23.

---

From the 1/4 section corner of sections 23 and 24, monumented with a mound of stone in N and S fence line. This position is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2N R3E  
1/4  
S23 | S24  
1995

Corner is located about 15 lks. N of a small draw, draining NW.

N. 89° 40.5' W., on the E-W center line of section 23.

- 39.665** Point for the center 1/4 section corner of section 23; not monumented.
- 40.534** Intersect the East Canyon Reservoir Boundary Line; not monumented.
- 59.259** Point for the center W 1/16 section corner, falls in East Canyon Reservoir; not monumented.
- 69.056** Point for the center W-W 1/64 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-W-W 1/64  
S23  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on E slope in sagebrush and native grass.

- 78.853** The 1/4 section corner of sections 22 and 23.
-

THE SUBDIVISION OF SECTION 23,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the W 1/16 section corner of sections 23 and 26.
- N. 0° 16.4' W., on the N-S center line of the SW 1/4 of section 23.
- 19.714** Point for the SW 1/16 section corner at intersection with the E-W center line of the SW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:
- T2N R3E  
SW 1/16  
S23  
1995
- Set a steel fence post alongside the aluminum post.
- Corner is located on E slope in sagebrush and native grass.
- 39.428** Point for the center W 1/16 section corner of section 23; not monumented.
- 
- From the point for the center S 1/16 section corner of section 23; not monumented.
- N. 89° 27.7' W., on the E-W center line of the SW 1/4 of section 23.
- 19.685** The SW 1/16 section corner.
- 39.370** Point for the S 1/16 section corner of sections 22 and 23; not monumented.
- 
- From the SW 1/16 section corner of section 23.
- N. 26° 34.8' W., on the East Canyon Reservoir Boundary Line in section 23.
- 22.106** The center W-W 1/64 section corner of section 23.
- 
- N. 26° 21.6' W., on the East Canyon Reservoir Boundary Line.
- 22.435** The N 1/16 section corner of sections 22 and 23.
- 
- From the intersect point on the line of Angle Point No. 7 and Angle Point No. 8, with the section line of sections 23 and 26; not monumented.
- N. 12° 11.1' W., on the East Canyon Reservoir Boundary Line.
- 18.195** Point for Angle Point No. 8, on ECR-Bdy.

THE SUBDIVISION OF SECTION 23,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-8 S23  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on W slope in sagebrush and native grass.

Thence N. 15° 28.4' W., on the ECR-Bdy.

**19.362** Intersect the N-S center line of section 23; not monumented.

**22.733** Intersect the E-W center line of section 23; not monumented.

**38.803** Point for Angle Point No. 9 of the ECR-Bdy.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-9 S23  
1995

Set a steel fence post alongside the aluminum post.

Corner is located on W slope in sagebrush and native grass.

Thence N. 31° 36.7' W., on the ECR-Bdy.

**29.194** The witness point and corner for Angle Point No. 10, on the section line between sections 14 and 23.

The Subdivision of Section 26,  
T. 2 N., R. 3 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 0° 16.5' E., on the N-S center line of section 26.

**34.251** Point for the center N-N-S 1/256 section corner; not monumented.

THE SUBDIVISION OF SECTION 26,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**39.144** Point for the center 1/4 section corner of section 26, at intersection with the E-W center line; not monumented.

**63.238** Intersect the East Canyon Reservoir Boundary Line; not monumented.

**78.492** The 1/4 section corner of sections 23 and 26.

---

From the point for the 1/4 section corner of sections 25 and 26; not monumented.

N. 89° 56.4' W., on the E-W center line of section 26.

**39.717** Point for the center 1/4 section corner of section 26; not monumented.

**47.707** Intersect the East Canyon Reservoir Boundary Line; not monumented.

**59.344** Point for the center W 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R3E  
C-W 1/16  
S26  
1995

Set a steel fence post alongside the aluminum post.

**78.971** The 1/4 section corner of sections 26 and 27.

---

From the point for the W 1/16 section corner of sections 26 and 35; not monumented.

N. 0° 03.3' E., on the N-S center line of the SW 1/4 of section 26.

**34.111** Point for the center N-N-SW 1/256 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T2N R3E  
C-N-N-SW 1/256  
S26  
1995

Set a steel fence post alongside the aluminum post.

Corner is located in bottom land about 52 lks. S of creek that drains ENE.

THE SUBDIVISION OF SECTION 26,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

38.984

The center W 1/16 section corner of section 26.

---

N. 0° 04.4' E., on the N-S center line of the NW 1/4 of section 26.

39.586

The W 1/16 section corner of sections 23 and 26.

---

From the center N-N-SW 1/256 section corner of section 26.

S. 89° 53.0' E., on the E-W center line of the N 1/2 of the NE 1/4 of the SW 1/4 of section 26.

9.664

Point for Angle Point No. 1 at intersection with the west right-of-way of State Highway No. 65, which is also the boundary of the East Canyon Reservoir.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-1 /  
S26  
1995

Set a steel fence post alongside the aluminum post.

Corner is in State Highway No. 65 right-of-way fence that bears NNE and SSW.

19.609

Point for the center N-N-S 1/256 section corner; not monumented.

---

From Angle Point No. 1, on the E-W center line of the N 1/2 of the NE 1/4 of the SW 1/4 of section 26.

Thence N. 22° 03.5' E., on the ECR-Bdy.

5.266

Intersect the E-W center line of section 26; not monumented.

13.727

Point for Angle Point No. 2.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-2 / S26  
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 26,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Corner is located in State Highway No. 65 right-of-way fence that bears NNE and SSW.

Thence N.  $14^{\circ} 31.5'$  E., on the ECR-B.

**2.892** Point for Angle Point No. 3, identical to the P.C. of curve, but not tangent of curve.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

ECR-B  
AP-3 / S26  
1995

Thence on curve to left, with:

Delta =  $9^{\circ} 16' 01''$ , R = 85.682, T = 6.944, L = 13.858,  
CB = N.  $17^{\circ} 25.5'$  E, and C = 13.843.

**13.858** Point for Angle Point No. 4, identical to P.T. of curve, falls in East Canyon Reservoir; not monumented.

Thence N.  $12^{\circ} 47.6'$  E., on the ECR-Bdy.

**0.245** Intersect the N-S center line of section 26; not monumented.

**6.189** Point for Angle Point No. 5, identical to a west highway right-of-way marker, monumented with a standard highway right-of-way brass cap marker, firmly set in concrete and marked:

CL100  
STA 1201 + 74.3  
ELV --  
1965

This position will also function as Angle Point No. 5.

Thence S.  $77^{\circ} 16.1'$  E., across State Highway No. 65 on the ECR-Bdy.

**2.273** Point for Angle Point No. 6, identical to an east highway right-of-way marker, monumented with a standard highway right-of-way brass cap marker, firmly set in concrete and marked:

CL75  
STA 1201 + 74.3  
ELV - 5752.59  
1965



THE SUBDIVISION OF SECTION 26,  
T. 2 N., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**


This position will also function as Angle Point No. 6.

---

Thence N.  $33^{\circ} 37.0'$  E., on the ECR-B.

**10.010** Point for Angle Point No. 7, on E side of State Highway 65.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:



Deposit a Deep 1 Magnet at base of aluminum post.

Corner is located on SSE slope and about 15 lks. NNW from the top of a spur, sloping WSW.

Thence N.  $12^{\circ} 11.1'$  W., on the ECR-Bdy.

**1.540** Intersect the section line between sections 23 and 26; not monumented.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

Name	Capacity
M. Ross Workman	Supervisory Cadastral Surveyor
Sandy Lewis	Cadastral Surveyor
Gregg Ostergaard	Survey Technician


## CERTIFICATE OF SURVEY

I, **Ronald K. Baugh, Supervisory Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the dates of the *1st day of June, 1992 and the 14th day of April, 1995*, I have dependently resurveyed a portion of the subdivisional lines, and the subdivision of sections 2, 3, 10, 11, 14, 15, 22, 23, and 26 *in Township 2 North, Range 3 East*,

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 22, 1997

Date



(Supervisory Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 2, 3, 10, 11, 14, 15, 22, 23, and 26, Township 2 North, Range 3 East, Salt Lake Meridian, Utah*,

executed by **Ronald K. Baugh, Supervisory Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

December 24, 1997

Date



(Chief Cadastral Surveyor for Utah)